


GLC-10000 Specifications

The specifications apply when the GLC-10000 is powered on for at least 30 minutes.




MD - A

UL1563




MD - B

UL1492/1310




MD - C1

IEC60990/61010-1




MD - C2

IEC60990/60598-1




MD - C3

IEC60990/62368-1




MD - D

IEC60598-1/62608-1




MD - E

General application




MD - F

IEC60601-1/UL2601-1




MD - G

IEC61010-1/GB4793.1




MD - H

IEC61010-1/62368-1




MD - I

JIS B8561/UL554NP



MD - PCC

MD - PCC



Note : The standard numbers that are listed are only example; the MD can be used with all applicable standards.

SPECIFICATION					
DC					
Ranges	Range	Resolution	Accuracy		
50.00mA	4.00mA～50.00mA	10μA	±(0.2%rdg+6dgt)		
5.000mA	0.400mA～5.000mA	1μA	±(0.2%rdg+6dgt)		
500.0μA	40.0μA～500.0μA	0.1μA	±(0.2%rdg+6dgt)		
50.00μA	4.00μA～50.00μA	0.01μA	±2.0%fs		
AC / AC+DC					
Ranges	Range	Resolution	Accuracy		
			0.1Hz≤ f ≤15Hz	15Hz< f ≤100kHz	100kHz< f ≤1MHz
50.00mA	4.00mA～50.00mA	10μA	±(4.0%rdg+10dgt)	±(2.0%rdg+6dgt)	±(2.0%rdg+10dgt)
5.000mA	0.400mA～5.000mA	1μA	±(4.0%rdg+10dgt)	±(2.0%rdg+6dgt)	±(2.0%rdg+10dgt)
500.0μA	40.0μA～500.0μA	0.1μA	±(4.0%rdg+10dgt)	±(2.0%rdg+6dgt)	±(2.0%rdg+10dgt)
50.00μA	4.00μA～50.00μA	0.01μA	±4.0%fs	±2.0%fs	±2.0%fs

AC Peak					
Ranges	Range	Resolution	Accuracy		
			15Hz≤ f ≤10kHz	10kHz< f ≤100kHz	100kHz< f ≤1MHz
75.0mA	5.0mA～75.0mA	100μA	±(2.0%rdg+6dgt)	±5%fs	±15%fs
7.500mA	0.500mA～7.500mA	1μA	±2.5%fs	±5%fs	±15%fs
750.0μA	4.0μA～750.0μA	0.1μA	±4%fs	±5%fs	±20%fs
EUT Voltage / Current Monitor					
Ranges	Range	Resolution	Accuracy		
300V	85V～300V	0.1V	±(5%rdg+10dgt)		
20A	0.5A～20A	0.1A	±(2%rdg+5dgt)		
Power Supply					
	For GLC-10000	AC 100V～240V, 50/60Hz			
	For EUT IN	AC 100V～240V, 50/60Hz , 20A			
	EUT OUT (Front)	AC 100V～240V, 50/60Hz , 10A			
	EUT OUT (Rear)	AC 100V～240V, 50/60Hz , 20A			
Interface					
	RS-232C, USB host & device, LAN, Signal I/O and GPIB (optional)				
Dimensions & Weight					
	342 (W) x 133.87 (H) x 348.51 (D); Approximately 7.5kg				